

ANFRAGE


+48 58 55 40 410

Standards:

DIN 766~,DIN 5685-A~



Beschichtung (Standard):



Maße							
Material index	D [mm]	L [mm]	P [mm]	B1 [mm]	Bmax [mm]	Obciążenie znamionowe [kg]	Obciążenie zrywające [kg]
63050150C5685M	1.5	15.5	12.5	2.5	7.0	10	40
6305090G766M	9.0	46,2	27.0	10.8	30.6	1000	4000
63050500C5685M	5.0	31.0	21.0	7.0	19.0	125	500
63051000C766M	10.0	60.0	28.0	14.0	38.0	1250	5000
6305100G766M	10.0	60.0	28.0	14.0	38.0	1250	5000
63050600C5685M	6.0	36.0	24.0	8.0	23.0	160	640
6305110G766M	11.0	53,8	31.0	13.2	37.4	1600	6400
63050200C5685M	2.0	16.0	12.0	2.5	7.5	20	80
6305040G766M	4.0	27.0	16.0	5.5	15.0	200	800
63050400C766M	4.0	27.0	16.0	5.5	15.0	200	800
63051300C766M	13.0	63.6	36.0	12.0	36.0	2000	8000
6305130G766M	13.0	63.6	36.0	12.0	47.0	2000	8000
6305050G766M	5.0	31.0	18.5	7.0	19.0	320	1250
63050800C5685M	8.0	48.0	32.0	11.0	30.0	320	1280
63050500C766M	5.0	31.0	18.5	7.0	19.0	320	1250
63050300C5685M	3.0	22.0	16.0	4.0	11.5	40	160
6305060G766M	6.0	36.0	18.5	8.0	23.0	400	1600
63050600C766M	6.0	36.0	18.5	8.0	23.0	400	1600

Material index	D [mm]	L [mm]	P [mm]	B1 [mm]	Bmax [mm]	Obciążenie znamionowe [kg]	Obciążenie zrywające [kg]
6305100OC5685M	10.0	60.0	40.0	14.0	38.0	500	2000
6305070G766M	7.0	42.0	22.0	9.5	26.0	630	2500
6305070OC766M	7.0	42.0	22.0	9.5	26.0	630	2500
6305040OC5685M	4.0	27.0	19.0	5.5	15.0	80	320
6305080G766M	8.0	41.0	24.0	11.0	30.0	800	3200
6305080OC766M	8.0	41.0	24.0	11.0	30.0	800	3200