


Standards:

DIN 766~,DIN 5685-A~



Beschichtung (Standard):



Maße							
Material index	D [mm]	L [mm]	P [mm]	B1 [mm]	Bmax [mm]	Obciążenie znamionowe [kg]	Obciążenie zrywające [kg]
63050400C5685M	4.0	27.0	19.0	5.5	15.0	80	320
63050800C5685M	8.0	48.0	32.0	11.0	30.0	320	1280
63051000C5685M	10.0	60.0	40.0	14.0	38.0	500	2000
63050300C5685M	3.0	22.0	16.0	4.0	11.5	40	160
63050150C5685M	1.5	15.5	12.5	2.5	7.0	10	40
63050600C5685M	6.0	36.0	24.0	8.0	23.0	160	640
63050200C5685M	2.0	16.0	12.0	2.5	7.5	20	80
63050500C5685M	5.0	31.0	21.0	7.0	19.0	125	500
6305070G766M	7.0	42.0	22.0	9.5	26.0	630	2500
6305090G766M	9.0	46,2	27.0	10.8	30.6	1000	4000
63051000C766M	10.0	60.0	28.0	14.0	38.0	1250	5000
6305050G766M	5.0	31.0	18.5	7.0	19.0	320	1250
6305110G766M	11.0	53,8	31.0	13.2	37.4	1600	6400
6305060G766M	6.0	36.0	18.5	8.0	23.0	400	1600
63051300C766M	13.0	63.6	36.0	12.0	36.0	2000	8000
63050600C766M	6.0	36.0	18.5	8.0	23.0	400	1600
6305130G766M	13.0	63.6	36.0	12.0	47.0	2000	8000
6305100G766M	10.0	60.0	28.0	14.0	38.0	1250	5000

Material index	D [mm]	L [mm]	P [mm]	B1 [mm]	Bmax [mm]	Obciążenie znamionowe [kg]	Obciążenie zrywające [kg]
6305040G766M	4.0	27.0	16.0	5.5	15.0	200	800
6305080G766M	8.0	41.0	24.0	11.0	30.0	800	3200
6305040OC766M	4.0	27.0	16.0	5.5	15.0	200	800
6305050OC766M	5.0	31.0	18.5	7.0	19.0	320	1250
6305070OC766M	7.0	42.0	22.0	9.5	26.0	630	2500
6305080OC766M	8.0	41.0	24.0	11.0	30.0	800	3200